

## DESCRIPTION

The **Micro-Sub 12** is a high output subwoofer designed for permanent installation. It uses a single 12" low frequency driver in a compact sealed enclosure.

Working in conjunction with external DSP processing, it achieves maximum bass output from a minimum enclosure size. DSP options include an Innovox proprietary powered system processor, or DSP configurations from our free library for Biamp, BSS and Symetrix processors.

The **Micro-Sub 12** complements the Innovox *Slim Line & SLA Series* of shallow profile surface-mount loudspeakers and the *Flex-Video Series* of display-mounted loudspeakers. It is also used as a low-bass component in extended range distributed audio systems.



(shown without grille)

### KEY FEATURES:

- very compact enclosure
- excellent transient response
- 32 Hz low frequency extension
- minimum depth (only 9.00 in.)

### APPLICATIONS:

- theme venues and restaurants
- boardrooms
- video presentation / program audio
- retail spaces

### NOMINAL DATA

Frequency Response	32 – 350 Hz ± 3 dB
Impedance	4 Ω
Power Handling	800 W long term program (AES-2)
Maximum Output	117 dB long term; 123 dB peak
Dimensions	height: 18.25" / 464 mm width: 14.13" / 359 mm depth: 9.00" / 229 mm
Net Weight	29 lbs / 13.2 kg
Shipping Weight	34 lbs / 15.4 kg

### DESCRIPTIVE DATA

System Configuration	Dedicated subwoofer
Components & Loading	(1) 12" LF driver, sealed
Recommended High-Pass Filter	4 <sup>th</sup> order Butterworth @ 28 Hz
Cabinet Type	Rectangular, sealed
Enclosure Material	Hardwood multi-ply plywood
Finish	Black or White (custom colors available)
Connectors	2-pole Phoenix
Suspension Hardware	(4) 3/8"-16 threaded mounting points located on enclosure sides & back
Grille	Powder-coated perforated steel standard

**DIMENSIONAL DRAWINGS**

