

DESCRIPTION

The **Micro-Sub 2x6** is a high definition subwoofer designed for permanent installation. It uses two 6" low frequency drivers in a very compact sealed enclosure.

Working in conjunction with external DSP processing, it achieves maximum bass output from a minimum enclosure size. DSP options include an Innovox proprietary powered system processor, or DSP configurations from our free library for Biamp, BSS and Symetrix processors..

The **Micro-Sub 2x6** complements the Innovox *Slim Line Series* of shallow profile surface-mount loudspeakers and the *Flex-Video Series* of display-mounted loudspeakers.



(shown without grille)

KEY FEATURES:

- ultra-compact enclosure
- Excellent transient response
- 45 Hz low frequency extension
- minimum depth (only 4.10 in.)

APPLICATIONS:

- theme venues and restaurants
- boardrooms
- video presentation / program audio
- retail spaces

NOMINAL DATA

Frequency Response	45 – 350 Hz ± 3 dB
Impedance	4 Ω (16 Ω available)
Power Handling	350 W long term program (AES-2)
Maximum Output	108 dB long term; 112 dB peak
Dimensions	height: 20.25" / 514 mm width: 14.13" / 359 mm depth w/ grille: 4.10" / 104 mm depth, no grille: 3.92" / 100 mm
Net Weight	18 lbs / 8.2 kg
Shipping Weight	21 lbs / 9.5 kg

DESCRIPTIVE DATA

System Configuration	Dedicated low frequency
Components & Loading	(2) 6" LF drivers, sealed
Recommended High-Pass Filter	4 th order Butterworth @ 40 Hz
Cabinet Type	Rectangular, sealed
Enclosure Material	Hardwood multi-ply plywood
Finish	Black or White (custom colors available)
Connectors	Dual binding head screws
Suspension Hardware	(2) 1/4"-20 threaded mounting points

DIMENSIONAL DRAWINGS

