

## DESCRIPTION

The **SL-1.1R** is a slim 2-way loudspeaker designed to be surface-mounted and disappear into the architectural surroundings. It employs a 1" textile dome HF driver and a 4" long-excursion LF driver to yield a very smooth, neutral response for near-field applications.


The addition of an available SBC-110 ceiling mounted sub-woofer extends low frequency response to 34 Hz and increases maximum system SPL.

### KEY FEATURES:

- slim profile (only 2" deep by 4" wide)
- 120° H x 120° V coverage
- blends into architectural environment
- easily integrated into architectural casework with optional millwork adapter kit

### APPLICATIONS:

- sound for video presentation
- home theater LCR
- home theater surrounds
- stage-lip / front-fill
- compact personal monitor



## NOMINAL DATA

Frequency Response	130 – 20,000 Hz ± 3 dB
Sensitivity	89 dB @ 2.83 volts / 1M
Impedance	8Ω
Power Handling	45 W long term program
Maximum Output	103 dB long term / 109 dB peak @ 1 meter on axis
Nominal Coverage Angles	120° H x 120° V
Dimensions	height: 10.50 " / 267 mm width: 4.56 " / 116 mm depth: 2.06 " / 52 mm
Net Weight	4.2 lbs / 1.9 kg
Shipping Weight	5.2 lbs / 2.4 kg

## DESCRIPTIVE DATA

System Configuration	Low profile 2-way
Components & Loading	(1) 4" long-excursion LF driver, (1) 1" textile dome HF
High-Pass Filter	Built-in 1 <sup>st</sup> order @ 120 Hz
Enclosure Type	Sealed enclosure, very low profile
Enclosure Material	Steel chassis, with composite endcaps
Finish	Black or White (custom colors available)
Connectors	Dual binding head screws
Suspension Hardware	Mounting brackets included
Grille	Integral, fabric wrapped