



AMERICAN LOUDSPEAKER INNOVATION

FLEX SELECT Series –

FS-V2

Key Features

- Custom built to match the exact height of your flat panel display
- Ultra slim profile – only two inches deep
- High resolution drivers for precise vocal articulation
- Can be used with an optional Innovox sub-bass in 2.1 applications

(shown without grilles)

DESCRIPTION

The *Flex Select* Model **FS-V2** is an ultra slim vertical speaker pair designed to mate with flat panel video displays. It has been designed for applications where the budget allows the use of separate amplifiers external to video displays. Carefully selected drivers are employed with sophisticated filter networks to take full advantage of the reserve power available with separate amplifiers to optimize performance and SPL in a slim profile. Nominal coverage angle is 120° H x 100° V. Configuration per channel includes two 3.5" long-excursion LF drivers and one .75" textile dome HF driver.

NOMINAL DATA

Frequency Response	120 – 20,000 Hz ± 3 dB
Sensitivity	90 dB @ 2.83 volts / 1M
Impedance	8 Ω
Power Handling	90 watts long-term (AES-2) (per channel)
Maximum Output	103 dB long-term, 109 dB peak
Nominal Coverage Angles	120° H x 100° V
Dimensions	height: (custom 19.0 – 60.0 ") width: 4.1 " depth: 2.1 "
Net Weight	10-17 lbs per pair (depending on height)
Shipping Weight	13-20 lbs per pair (depending on height)

DESCRIPTIVE DATA

System Configuration	Low profile custom-sized side-mount speaker for flat-panel displays
Components & Loading (per channel)	(2) 3.5" woofers; (1) 0.75" soft-dome tweeter
Recommended High-Pass Filter	On-board 1 st order @ 120 Hz; no outboard HP needed
Cabinet Type	Very low profile, sealed, integral grille
Enclosure Material	Extruded ABS plastic with steel baffle plate
Finish	Black is standard; (custom colors available)
Connectors	Phoenix
Grille	Integral fabric wrap

296 North Pascal Street
Saint Paul MN 55104

innovoxaudio.com

PROUDLY MADE IN THE U.S.A.