

## DESCRIPTION

The **SL-4.1US** is an ultra-slim 2-way loudspeaker designed to be surface-mounted flat on a wall and disappear into the architectural surroundings. Its precision ribbon HF driver and four 4" long-excursion LF drivers renders complex audio program with detail and clarity that does not seem possible from such a small package.

The addition of an available SBC-210 ceiling mounted sub-woofer extends low frequency response to 34 Hz and increases maximum system SPL.

### KEY FEATURES:

- ultra-slim profile (only 1.6" deep)
- 120° H x 90° V coverage
- employs precision ribbon HF driver
- blends into architectural environment
- hidden mounting bracket

### APPLICATIONS:

- sound for video presentation
- premium home theater LCR
- premium home theater surrounds
- delay fill
- theatrical effects



## NOMINAL DATA

Frequency Response	120 – 20,000 Hz ± 3 dB
Sensitivity	92 dB @ 2.83 volts / 1M
Impedance	8Ω
Power Handling	150 W long term program
Maximum Output	111 dB peak / 117 dB peak @ 1 meter
Nominal Coverage Angles	120° H x 90° V
Dimensions	height: 30.75 " / 781 mm width: 6.75 " / 171 mm depth: 1.75 " / 44 mm
Net Weight	11.0 lbs / 5.0 kg
Shipping Weight	13.9 lbs / 6.3 kg

## DESCRIPTIVE DATA

System Configuration	Low profile 2-way full-range
Components & Loading	(4) 4 " woofers; (1) ribbon tweeter
High-Pass Filter	Built-in 1 <sup>st</sup> order @ 120 Hz
Enclosure Type	Sealed enclosure, ultra-slim profile
Enclosure Material	Steel chassis, with composite endcaps
Finish	Black or White standard; (custom colors available)
Connectors	Dual binding head screws
Suspension Hardware	Hidden bracket included
Grille	Integral, fabric wrapped; optional perforated metal grille