

## DESCRIPTION

The **HLA-Stage Lip** is a companion loudspeaker specifically designed to work in conjunction with an HLA hybrid line array to better serve front row seats. It provides both enhanced articulation and helps to localize the apparent sound source with performers on stage.

A 6" ribbon HF driver and two 3.5" MF drivers are employed to match the clarity, detail and program level of other HLA loudspeakers. The enclosure's shallow depth allows easy integration into the architectural environment.

### KEY FEATURES:

- front row MF/HF fill in auditoriums
- 30° V x 120° H coverage
- very thin profile (2 inches deep)
- 140 Hz to 20kHz (± 3 dB)
- 111 dB long term output



## NOMINAL DATA

Frequency Response	140 – 20,000 Hz, ± 3 dB
Sensitivity	90 dB @ 2.83V / 1M
Impedance	16Ω (70-volt transformer available)
Power Handling	150 W long-term (AES-2)
Maximum Output	111 dB long-term, 117 dB peak
Nominal Coverage Angles	120° H x 30° V
Dimensions	height: 7.36" / 187 mm width: 12.13" / 308 mm depth: 2.45" / 62 mm
Net Weight	8.6 lbs / 3.9 kg
Shipping Weight	11.0 lbs / 5.0 kg

## DESCRIPTIVE DATA

System Configuration	Passive 2-way
Components & Loading	(2) 3.5" MF (1) 6" ribbon HF
Recommended High-Pass Filter	4 <sup>th</sup> order Butterworth @ 200 Hz
Enclosure Type	Sealed
Enclosure Material	Steel, aluminum & Baltic Birch plywood
Finish	Black or White standard (custom colors available)
Connectors	(2) dual binding head screws
Included Hardware	Steel yoke
Grille	Painted perforated steel

**DIMENSIONAL DRAWINGS**

