

DESCRIPTION

The Slim Line **SL-Micro** is a slim 2-way loudspeaker designed to be surface- or flush-mounted and disappear into the architectural surroundings. It employs a 3/4" textile dome HF driver and two 2" long-excursion LF drivers to yield a very smooth, neutral response for near-field applications.

The addition of an available SB-206 surface or in-wall sub-woofer extends low frequency response to 44 Hz and increases maximum system SPL.

KEY FEATURES:

- slim profile (only 2.0" deep by 2.5" wide)
- 120° H x 90° V coverage
- blends into architectural environment
- easily integrated into architectural casework with optional millwork adapter kit

APPLICATIONS:

- sound for video presentation
- LCR center channel
- video conferencing
- compact personal monitor



NOMINAL DATA

Frequency Response	150 – 20,000 Hz ± 3 dB
Sensitivity	84 dB @ 2.83 volts / 1M
Impedance	8Ω (70V transformer available)
Power Handling	45 W long term program
Maximum Output	100 dB long term / 106 dB peak @ 1 meter on axis
Nominal Coverage Angles	120° H x 90° V
Dimensions	height: 13.00 " / 330 mm width: 2.50 " / 64 mm depth: 2.00 " / 51 mm
Net Weight	2.5 lbs / 1.2 kg
Shipping Weight	3.0 lbs / 1.4 kg

DESCRIPTIVE DATA

System Configuration	Low profile 2-way
Components & Loading	(2) 2" long-excursion LF drivers, (1) 3/4" textile dome HF
High-Pass Filter	Built-in 1 st order @ 130 Hz
Enclosure Type	Sealed enclosure, very low profile
Enclosure Material	Aluminum chassis, with composite endcaps
Finish	Black or White (custom colors available)
Connectors	Dual binding head screws
Suspension Hardware	Mounting brackets included
Grille	Perforated metal