

DESCRIPTION

The **SB-115** is a very compact sub-bass module designed for permanent installation. It employs a 15-inch long-excursion driver in an optimally tuned vented enclosure which can be suspended from internal fly points, or positioned on the floor.

The **SB-115** is an ideal choice for applications requiring precise transient response and low bass extension. It's compact size fits well under stages, on stage and in flown arrays.



(shown with grille removed)

KEY FEATURES:

- compact size
- bass extension to 34Hz
- very high output
- low power compression
- excellent transient response

APPLICATIONS:

- churches
- performing arts centers
- cinema
- night clubs

NOMINAL DATA

| | |
|-------------------------|--|
| Frequency Response | 34 – 350 Hz ± 3 dB |
| Sensitivity | 95 dB @ 2.83 volts / 1M (in operating band) |
| Impedance | 8 Ω |
| Power Handling | 1000 W long term (AES-2) |
| Maximum Output | 123 dB long term; 129 dB peak |
| Nominal Coverage Angles | omni-directional |
| Dimensions | height: 17.25 " / 438 mm width: 18.50 " / 470 mm depth: 25.00 " / 635 mm |
| Net Weight | 90 lbs / 40.9 kg |
| Shipping Weight | 117 lbs / 53.2 kg |

DESCRIPTIVE DATA

| | |
|------------------------------|---|
| System Configuration | Dedicated sub-bass |
| Components & Loading | (1) 15 " long-excursion cone driver |
| Enclosure Type | Optimally tuned, vented |
| Recommended High-Pass Filter | 4 th order Butterworth @ 27 Hz |
| Enclosure Material | Hardwood multi-ply plywood |
| Finish | Black or White (custom finishes available) |
| Connectors | NL-4 & Dual binding head screws |
| Suspension Hardware | (8) 3/8"-16 threaded mounting points located on enclosure top, sides, back |
| Grille | Powder coated perforated steel grille |

West Coast Office

1155-C Arnold Drive, #231
Martinez CA 94553
ph: **925 372-8156**
email: orders@innovoxaudio.com

Central Office

296 North Pascal Street
Saint Paul MN 55104
ph: **612 379-0100**
email: sales@innovoxaudio.com

DIMENSIONAL DRAWINGS

