

DESCRIPTION

The **SB-115** is a very compact sub-bass module designed for permanent installation. It employs a 15-inch long-excursion driver in an optimally tuned vented enclosure which can be suspended from internal fly points, or positioned on the floor.

The **SB-115** is an ideal choice for applications requiring precise transient response and low bass extension. It's compact size fits well under stages, on stage and in flown arrays.



(shown with grille removed)

KEY FEATURES:

- compact size
- bass extension to 34Hz
- very high output
- low power compression
- excellent transient response

APPLICATIONS:

- churches
- performing arts centers
- cinema
- night clubs

NOMINAL DATA

Frequency Response	34 – 350 Hz \pm 3 dB
Sensitivity	95 dB @ 2.83 volts / 1M (in operating band)
Impedance	8 Ω
Power Handling	1000 W long term (AES-2)
Maximum Output	123 dB long term; 129 dB peak
Nominal Coverage Angles	omni-directional
Dimensions	height: 17.25 " / 438 mm width: 18.50 " / 470 mm depth: 25.00 " / 635 mm
Net Weight	90 lbs / 40.9 kg
Shipping Weight	117 lbs / 53.2 kg

DESCRIPTIVE DATA

System Configuration	Dedicated sub-bass
Components & Loading	(1) 15 " long-excursion cone driver
Enclosure Type	Optimally tuned, vented
Recommended High-Pass Filter	4 th order Butterworth @ 27 Hz
Enclosure Material	Hardwood multi-ply plywood
Finish	Black or White (custom finishes available)
Connectors	NL-4 & Dual binding head screws
Suspension Hardware	(8) 3/8"-16 threaded mounting points located on enclosure top, sides, back
Grille	Powder coated perforated steel grille

West Coast Office

1155-C Arnold Drive, #231
Martinez CA 94553
ph: **925 372-8156**
email: orders@innovoxaudio.com

Central Office

296 North Pascal Street
Saint Paul MN 55104
ph: **612 379-0100**
email: sales@innovoxaudio.com

DIMENSIONAL DRAWINGS

