

Installation Sub-Woofer

The SB-115 is a very compact sub-bass module designed for permanent installation. It employs a 15-inch long-excursion driver in an optimally tuned vented enclosure which can be suspended from internal fly points or positioned on the floor.

The SB-115 is an ideal choice for applications requiring precise transient response and low bass extension. Its compact size fits well under stages, on stage, and in flown arrays.



Key Features

- Compact size
- Bass extension to 34 Hz
- Very high output
- Excellent transient response

Applications

- Churches
- Performing Arts Centers
- Cinema
- Night Clubs

Description

System Configuration	Dedicated sub-bass
Components & Loading	(1) 15" long-excursion cone driver
Recommended High-Pass Filter	4th order Butterworth @ 34 Hz
Input Connectors	NL-4 & dual binding head screws
Enclosure Type	Optimally tuned, vented
Enclosure Material	Hardwood multi-ply plywood
Finish	Black or White standard (custom colors available)
Suspension Hardware	(8) 3/8-16 threaded mounting points located on enclosure top, sides & back
Grille	Painted perforated steel

Nominal Data

Frequency Response	34 – 350 Hz ± 3 dB
Sensitivity	95 dB @ 2.83 volts / 1M (in operating band)
Impedance	8 Ω
Power Handling	1000 W long-term (AES-2)
Maximum Long-Term Output	123 dB @ 1M
Peak Output	129 dB @ 1M
Nominal Coverage Angles	Omni-directional
Dimensions Height	17.25" / 438 mm
Width	17.25" / 438 mm
Depth	27.63" / 702 mm
Net Weight	90 lbs / 40.9 kg
Shipping Weight	117 lbs / 53.2 kg

Sub-Bass Series

SB-115



Installation Sub-Woofers

