

# FP-V2 P



Flex Precision™ Series

EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## Made-to-Measure for the Exact Width of Your Flat Panel Display

### DESCRIPTION

The **Flex Precision FP-V2 P** is a display mounted single-channel horizontal loudspeaker that employs ribbon HF and extended range LF drivers in an ultra slim enclosure. Its frequency response (120-20,000 Hz  $\pm$ 3 dB) has been optimized for speech intelligibility.

Flex Precision loudspeakers can be used in combination with an Innovox Micro-Sub Series sub-woofer to extend low frequency response below 50 Hz to support full-range music program.



### KEY FEATURES

- Made to match the height of the display
- Works with Micro-Sub Series subwoofers
- 100 W class D power
- Ribbon HF provides superior speech quality

### APPLICATIONS

- Stereo video conference speaker
- Audio for digital signage
- Uniform sound coverage for near field applications

### DESCRIPTIVE DATA

System Configuration:	Frequency-shaded line array (sold in pairs)
Components & Loading:	(4) 3.5" long-excursion LF drivers; (1) 3.25" ribbon HF driver
Recommended High-Pass:	4 <sup>th</sup> order Butterworth @ 100 Hz
Enclosure Type:	Sealed enclosure, low-profile column
Enclosure Material:	Extruded ABS with steel baffle plate
Finish:	Black fabric
Connectors:	3-pole Phoenix, 2-pole Phoenix
Suspension:	Adjustable universal mounting system for direct mount to display
Grille:	Integral, fabric wrap, color black

### NOMINAL DATA

Frequency Response:	120 – 20,000 Hz $\pm$ 3 Db
Amplifier Power:	2 x 100 W RMS
Maximum Long-Term Output: Peak Output:	105 dB 111 dB
Nominal Coverage Angles:	120° H x 90° V
Minimum Display Height:	27.5" / 699 mm
Dimensions	Height: (custom) Width: 4.06" / 103 mm Depth: 2.13" / 54 mm
Approximate Net Weight/pair: (varies with length)	9 – 26 lbs. / 4.0 – 11.7 kg
Approximate Shipping Weight/pair: (varies with length)	13 – 30 lbs. / 5.8 – 13.6 kg

# FP-V2 P

Flex Precision™ Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## DIMENSIONAL DRAWINGS

