

FF-H1.625 P

Powered Flex Focus™ Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

Horizontal Line Array Solution for Larger Rooms

DESCRIPTION

The **FF-H1.625 P** loudspeaker employs shaded line array technology with ribbon high frequency drivers to extend sound projection in longer rooms. Its frequency response (120-20,000Hz \pm 3dB) is optimized for speech intelligibility and musical detail.

The FF-H1.625 P loudspeaker can be used in combination with an Innovox Micro-Sub Series subwoofer to extend low frequency response to support full-range music program. The FF-H1.625 P loudspeaker employs a 100-watt class D power amplifier.



KEY FEATURES

- Made to match width of video display
- Onboard 100-watt class D amplifier
- Precise 25° horizontal control
- Line Array projection for longer rooms

APPLICATIONS

- Mono Video Conference speaker
- Audio for Digital signage
- Managed sound coverage for museum displays

DESCRIPTIVE DATA

| | |
|--|--|
| System Configuration: | Frequency-shaded line array |
| Components & Loading: | (6) 3.5 " LF drivers; (1) HF ribbon |
| Enclosure Type: | Sealed enclosure, low profile column |
| Enclosure Material: | ABS with ABS endcaps |
| Inputs: | Balanced Line & Unbalanced Stereo |
| Connectors: | 3-pole Phoenix & 3.5mm stereo |
| Suspension Options: <i>(specify #1 or #2 when ordering)</i> | #1 – Adjustable universal bracket for direct mount to display #2 – Wall-mount |
| Grille: | Integral, fabric wrapped, color black |

NOMINAL DATA

| | |
|---|---|
| Frequency Response: | 120 – 20,000 Hz \pm 3 dB |
| Nominal Coverage Angles: | 25° H x 120° V |
| Pattern Control to: | 650 Hz |
| Maximum Long-Term Output: Peak Output: | 113 dB 119 dB |
| Minimum Display Width: | 46.5"/1181 mm |
| Dimensions | Height: 4.06" / 103 mm Width: (custom) Depth: 2.13" / 54 mm |
| Approximate Net Weight: | 14.0-26.0 lbs. / 6.4-11.8 kg |
| Approximate Shipping Weight: | 18.0-30.0 lbs. / 8.2-13.6 kg |

FF-H1.625 P

Flex Focus™ Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

