

FF-V2.10 P | FF-V2.10 LAC P

Powered Flex Focus™ Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

A Line Array Solution for Larger Rooms

DESCRIPTION

The **FF-V2.10 P** loudspeaker pairs use shaded line array technology with ribbon high frequency drivers to extend sound projection in longer rooms. Its frequency response (120 Hz – 20 kHz ± 3 dB) is optimized for speech intelligibility and musical detail. They are available in two configurations: FF V2.10 P for monitors that are mounted at a standard viewing height, and FF-V2.10 P LAC (Lowered Acoustic Center) for monitors that are mounted above standard viewing height.

The FF-V2.10 P loudspeaker pairs use a stereo 100 watt per channel class D power amplifier. The FF-V2.10 P loudspeaker pairs can be used in combination with an Innovox Micro-Sub Series sub-woofer to extend low frequency response to support full-range music program.



KEY FEATURES

- Made to match height of video display
- 100 watt per channel stereo power amplifier
- Precise 120°H x 25°V control
- Line Array projection for longer rooms

APPLICATIONS

- Mono video conference speaker
- Audio to complement digital signage
- 2.1 System in combination with MicroSub subwoofer

DESCRIPTIVE DATA

System Configuration:	Frequency-shaded line array
Components & Loading:	(10) 3.5" LF drivers; (1) HF ribbon
Enclosure Type:	Sealed enclosure, low profile column
Enclosure Material:	ABS with ABS endcaps
Inputs:	Balanced Line , Unbalanced Stereo
Connectors:	6-pole Phoenix & 3.5mm stereo
Suspension Options: <i>(specify #1 or #2 when ordering)</i>	#1 – Adjustable universal bracket for direct mount to display #2 – Wall-mount
Grille:	Integral, fabric wrapped, color black

NOMINAL DATA

Frequency Response:	120 Hz – 20 kHz ± 3 dB
Nominal Coverage Angles:	120° H x 25° V
Maximum Long-Term Output: Peak Output:	114 dB 120 dB
Minimum Height:	66" / 1676 mm
Dimensions	Height: (custom) Width: 4.06" / 103 mm Depth: 2.13" / 54 mm
Approximate Net Weight:	18.0-35.0 lbs. / 8.2-15.9 kg
Approximate Shipping Weight:	22.0-39.0 lbs. / 10.0-17.7 kg

FF-V2.10 P | FF-V2.10 LAC P

Powered Flex Focus™ Series

EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

