

FF-V2.10 PXD | FF-V2.10 LAC PXD

Powered Flex Focus Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

Vertical Line Array Solution for Longer Rooms

DESCRIPTION

The **FF-V2.10 PXD** loudspeaker pairs use shaded line array technology with ribbon high frequency drivers to extend sound projection in longer rooms. Their frequency response (120 Hz – 20 kHz ± 3 dB) is optimized for speech intelligibility and musical detail.

They are available in two configurations: FF-V2.10 PXD for monitors that are mounted at a standard viewing height and FF-V2.10 PXD LAC (Lowered Acoustic Center) for monitors that are mounted above standard viewing height.

The FF-V2.10 PXD loudspeaker pairs use a stereo 100-watt per channel class D amplifier with pre-amp, DSP, Ethernet control and Dante. Adding an Innovox Flex-Companion Series powered sub-woofer will extend low frequency performance below 50 Hz to deliver high impact full-range music program.



KEY FEATURES

- Made to match height of video display
- 2 x 100W class D power and DSP with Dante
- Precise 120° H x 25° V coverage pattern
- Line Array projection for longer rooms

APPLICATIONS

- Stereo video conference speaker
- Stereo Sound to complement digital signage
- 2.1 System with Flex-Companion Series subwoofer

DESCRIPTIVE DATA

System Configuration:	Frequency-shaded line array Sold in pairs
Components & Loading:	(10) 3.5" LF drivers; (1) HF ribbon
Enclosure Type:	Sealed enclosure, low profile column
Enclosure Material:	ABS with ABS endcaps
Inputs:	Balanced Line, Unbalanced Stereo, Optical Digital, Speaker Level, USB and Dante
Outputs:	Processed Sub-Bass & Microphone
Control:	IR, RS 232, USB ; Ethernet
Connectors:	(2) 6-pole Phoenix, 3.5mm stereo, Toslink, USB (2) RJ-45 Dante, Ethernet
Suspension Options: <i>(specify #1 or #2 when ordering)</i>	#1 – Adjustable universal bracket for direct mount to display #2 – Wall-mount
Grille:	Integral, fabric wrapped, color black

NOMINAL DATA

Frequency Response:	120 – 20,000 Hz ± 3 dB
Nominal Coverage Angles:	120° H x 25° V
Maximum Long-Term Output: Peak Output:	114 dB 120 dB
Minimum Height:	66" / 1676 mm
Dimensions	Height: (custom) Width: 4.06" / 103 mm Depth: 2.13" / 54 mm
Approximate Net Weight:	18.0-35.0 lbs / 8.2-15.9 kg
Approximate Shipping Weight:	22.0-39.0 lbs / 10.0-17.7 kg

FF-V2.10 PXD | FF-V2.10 LAC PXD

Powered Flex Focus™ Series



EXPERIENCE THE SOUND OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

