## FF-V2.4 PXD

## Powered Flex Focus Series



EXPERIENCE THE SOUND OF TRUE ENGAGEMENT

## Vertical Line Array Solution for Longer Rooms

#### **DESCRIPTION**

The **FF-V2.4 PXD** loudspeaker pairs use shaded line array technology with ribbon high frequency drivers to extend sound projection in longer rooms. Their frequency response (120 Hz - 20 kHz  $\pm$  3 dB) is optimized for speech intelligibility and musical detail.

FF-V2.4 PXD loudspeaker pairs employ a stereo 100-watt per channel class D amplifier with preamp, DSP, Ethernet control, and Dante.

Adding an Innovox Flex-Companion Series powered sub-woofer will extend low frequency performance below 50Hz to deliver high impact full-range music program.

KEY FEATURES		APPLICATIONS	
•	Made to match height of video display	•	Stereo Video Conference speaker

- made to mater meight of video display
- 2 x 100W class D power and DSP with Dante 

   Audio to complement Digital signage
- Precise 120° H x 25° V coverage pattern
   Line Array projection for longer rooms

  2.1 System in combination with MicroSub subwoofer



#### **DESCRIPTIVE DATA**

System Configuration:	Frequency-shaded line array   Sold in pairs
Components & Loading:	(4) 3.5 " LF drivers; (1) HF ribbon
Enclosure Type:	Sealed enclosure, low profile column
Enclosure Material:	ABS with ABS endcaps
Inputs:	Balanced Line, Unbalanced Stereo, Optical Digital, Speaker Level, USB, Dante
Outputs:	Processed Sub-Bass
Control:	IR, RS 232, USB; Ethernet
Connectors:	6-pole Phoenix, 3.5mm stereo, Toslink, USB and Ethernet
Suspension Options:	#1 – Adjustable universal bracket for direct mount to display
(specify #1 or #2 when ordering)	#2 – Wall-mount
Grille:	Integral, fabric wrapped, color black

#### **NOMINAL DATA**

Frequency Response:		120 - 20,000 Hz ± 3 dB
		120° H x 25° V
Maximum Long-Term Output: Peak Output:		113 dB 119 dB
Minimum Height:		37" / 940 mm
Dimensions	Height: Width: Depth:	(custom) 4.06" / 103 mm 2.13" / 54 mm
Approximate Net Weight:		12.0 – 29.0 lbs. / 5.4 – 31.1 kg
Approximate Shipping Weight:		16.0-33 lbs. / 7.3-15.0 kg

# FF-V2.4 PXD

## Powered Flex Focus<sup>™</sup> Series



#### **DIMENSIONAL DRAWINGS**





