

# FF-V2.4 PX

Powered Flex Focus Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## Vertical Line Array Solution for Larger Rooms

### DESCRIPTION

The **FF-V2.4 PX** loudspeaker pairs use shaded line array technology with ribbon high frequency drivers to extend sound projection in longer rooms. Its frequency response (120Hz – 20 kHz ± 3 dB) is optimized for speech intelligibility and musical detail.

The FF-V2.4 PX loudspeaker pairs employ a stereo 100-watt per channel class D amplifier with pre-amp and DSP.

Adding an Innovox Flex-Companion Series powered sub-woofer will extend low frequency performance below 50 Hz to deliver high impact full-range music program.



### KEY FEATURES

- Made to match height of video display
- 100 watt per channel stereo power amplifier
- Precise 120°H x 25° V control
- Line Array projection for longer rooms

### APPLICATIONS

- Stereo Video Conference speaker
- Audio to complement Digital signage
- 2.1 System in combination with MicroSub subwoofer

### DESCRIPTIVE DATA

System Configuration:	Frequency-shaded line array   Sold in pairs
Components (pre array):	(4) 3.5" LF drivers; (1) HF ribbon
Enclosure Type:	Sealed enclosure, low profile column
Enclosure Material:	ABS with ABS endcaps
Inputs:	Balanced Line, Unbalanced Stereo, Optical Digital, Speaker Level, USB
Outputs:	Processed Sub-Bass
Connectors:	2-pole Phoenix
Suspension Options: <i>(specify #1 or #2 when ordering)</i>	#1 – Adjustable universal bracket for direct mount to display #2 – Wall-mount
Grille:	Integral, fabric wrapped, color black

### NOMINAL DATA

Frequency Response:	120 Hz – 20 k Hz ± 3 dB
Sensitivity:	95 dB @ 2.83V / 1M
Nominal Coverage Angles:	120° H x 25° V
Pattern Control to:	900 Hz
Nominal Impedance:	4Ω
Long-Term Power Handling:	175 W (AES-2)
Maximum Long-Term Output: Peak Output:	116 dB 122 dB
Minimum Display Height:	28" / 711 mm
Dimensions	Height: (custom) Width: 4.06" / 103 mm Depth: 2.13" / 54 mm
Approximate Net Weight:	12.0 – 29.0 lbs / 5.4 – 31.1 kg
Approximate Shipping Weight:	16.0-33 lbs / 7.3-15.0 kg

# FF-V2.4 PX

Flex Focus™ Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## DIMENSIONAL DRAWINGS

