

FF-V2.4

Flex Focus™ Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

A Line Array Solution for Larger Rooms

DESCRIPTION

Flex Focus loudspeakers employ shaded line array technology with precision ribbon HF drivers to extend sound projection in longer meeting rooms. Their frequency response (120 Hz – 20kHz ± 3 dB) has been optimized for speech intelligibility.

Flex Focus loudspeakers can be used in combination with an Innovox Micro-Sub Series sub-woofer to extend low frequency response to support full-range music program.



KEY FEATURES

- Made to match height of video display
- Precise 120° H x 25° V control
- Line Array projection for longer rooms

APPLICATIONS

- Stereo Video Conference speaker
- Audio to complement Digital signage
- 2.1 System in combination with MicroSub subwoofer

DESCRIPTIVE DATA

System Configuration:	Frequency-shaded line array (sold in pairs)
Components & Loading:	(4) 3.5" LF drivers; (1) HF ribbon
Enclosure Type:	Sealed enclosure, low profile column
Enclosure Material:	ABS with ABS endcaps
Connectors:	2-pole Phoenix
Suspension Options: <i>(specify #1 or #2 when ordering)</i>	#1 – Adjustable universal bracket for direct mount to display #2 – Wall-mount
Grille:	Integral, fabric wrapped, color black

NOMINAL DATA

Frequency Response:	120 Hz – 20 k Hz ± 3 dB
Sensitivity:	95 dB @ 2.83V / 1M
Nominal Coverage Angles:	120° H x 25° V
Pattern Control to:	900 Hz
Nominal Impedance:	4Ω
Long-Term Power Handling:	175 W (AES-2)
Maximum Long-Term Output: Peak Output:	116 dB 122 dB
Minimum Display Height:	28" / 711 mm
Dimensions	Height: (custom) Width: 4.06" / 103 mm Depth: 2.13" / 54 mm
Approximate Net Weight:	12.0 – 29.0 lbs. / 5.4 – 31.1 kg
Approximate Shipping Weight:	16.0-33 lbs. / 7.3-15.0 kg

FF-V2.4

Flex Focus™ Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

