

FF-V2.6 PX | FF-V2.6 LAC PX

Powered Flex Focus Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

Vertical Line Array Solution for Larger Rooms

DESCRIPTION

The FF-V2.6 PX loudspeaker pairs use shaded line array technology with ribbon high frequency drivers to extend sound projection in longer rooms. Their frequency response (120 Hz – 20 kHz ± 3dB) is optimized for speech intelligibility and musical detail.

They are available in two configurations: FF-V2.6 PX for monitors that are mounted at a standard viewing height and FF-V2.6 PX LAC (Lowered Acoustic Center) for monitors that are mounted above standard viewing height.

FF-V2.6 vertical loudspeaker pairs employ a stereo 100-watt per channel class D amplifier with pre-amp and DSP. Adding an Innovox Flex-Companion Series powered sub-woofer will extend low frequency performance below 50Hz to deliver high impact full-range music program.



KEY FEATURES

- Made to match height of video display
- 2 x 100W class D power and DSP
- Precise 120° H x 25° V coverage pattern
- Line Array projection for longer rooms

APPLICATIONS

- Stereo video conference speaker
- Stereo Sound to complement digital signage
- 2.1 System with Flex-Companion Series subwoofer

DESCRIPTIVE DATA

System Configuration:	Frequency-shaded line array Sold in pairs
Components & Loading:	(6) 3.5" LF drivers; (1) HF ribbon
Enclosure Type:	Sealed enclosure, low profile column
Enclosure Material:	ABS with ABS endcaps
Inputs:	Balanced Line , Unbalanced Stereo, Optical Digital, Speaker Level, and USB
Outputs:	Processed Sub-Bass
Control:	IR, RS 232, USB
Connectors:	6-pole Phoenix, 3.5mm stereo, Toslink, and USB
Suspension Options: <i>(specify #1 or #2 when ordering)</i>	#1 – Adjustable universal bracket for direct mount to display #2 – Wall-mount
Grille:	Integral, fabric wrapped, color black

NOMINAL DATA

Frequency Response:	120 – 20,000 Hz ± 3 dB
Nominal Coverage Angles:	120° H x 25° V
Maximum Long-Term Output: Peak Output:	113 dB 119 dB
Minimum Height:	46" / 1168 mm
Dimensions	Height: (custom) Width: 4.06" / 103 mm Depth: 2.13" / 54 mm
Approximate Net Weight:	14.0-31 lbs / 3.7-14.1 kg
Approximate Shipping Weight:	18.0-35.0 lbs / 8.2-15.9 kg

FF-V2.6 PX | FF-V2.6 LAC PX

Powered Flex Focus™ Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS



