

Micro-Sub 12P



Micro-Sub Series


EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

Compact Powered Sub-Bass Loudspeaker

DESCRIPTION

The **Micro-Sub 12P** is a high definition powered subwoofer designed for permanent installation. It uses a 12" low frequency driver in a compact sealed enclosure and employs a 700-Watt PowerSoft Class D amplifier with on-board DSP to achieve superior transient response and maximum output.

The **Micro-Sub 12P** complements the Innovox *Slim Line* and *SLA Series* of shallow profile surface-mount loudspeakers, and the *Flex Video Series* of display-mounted loudspeakers. It also is used as a low-bass component in extended range distributed audio systems.



KEY FEATURES

- Very compact enclosure (only 9" deep)
- 700-watt Class D amplifier with DSP
- Excellent transient response
- LF extension to 32 Hz

APPLICATIONS

- Sound for video presentations
- Themed venues and restaurants
- Boardrooms
- Retail Spaces

DESCRIPTIVE DATA

System Configuration:	Dedicated low frequency
Components:	(1) 12" LF driver
Recommended High-Pass Filter:	4 th order Butterworth @35 Hz
Cabinet Type:	Rectangular, sealed enclosure
Enclosure Material:	Hardwood multi-ply plywood
Finish:	Black or White (custom colors available)
Connectors:	XLR
Suspension Hardware:	(2) 1/4"-20 threaded mounting points
Grille:	Painted perforated steel

NOMINAL DATA

Frequency Response:	32 – 350 Hz \pm 3 dB
Class D Power:	700 W RMS
Maximum Long-Term Output:	117 dB
Peak Output:	123 dB
Dimensions	Height: 23.125" / 587 mm
	Width: 14.625" / 371 mm
	Depth: 9.00" / 229 mm
Net Weight:	43 lbs / 19.5 kg
Shipping Weight:	47 lbs / 21.4 kg

Micro-Sub 12P

Micro-Sub Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

