

Micro-Sub 2x6C



Micro-Sub Series


EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

Compact Sub-Bass Loudspeaker for Install in 2' x 2' ACT Ceilings

DESCRIPTION

The **Micro-Sub 2x6C** is a high definition subwoofer designed for permanent installation. It uses two 6.5" low frequency drivers in a very compact sealed enclosure. It should be used in conjunction with out-board active equalization to achieve superior transient response and maximum output. This sophisticated DSP processing can be provided by an Innovox proprietary powered system processor.

The **Micro-Sub 2x6C** complements the Innovox *Slim Line Series* of shallow profile surface-mount loudspeakers and the *Flex Video Series* of display-mounted loudspeakers. It also is used as a low-bass component in extended range distributed audio systems.



KEY FEATURES

- Mounts in 2'x2' ceiling grid
- Very compact enclosure (only 4.75" deep)
- Excellent transient response
- LF extension to 45Hz

APPLICATIONS

- Sound for video presentations
- Themed venues and restaurants
- Boardrooms
- Retails Spaces

DESCRIPTIVE DATA

System Configuration:	Dedicated low frequency
Components:	(2) 6.5" LF drivers
Recommended High-Pass Filter:	4 th order Butterworth @46 Hz
Cabinet Type:	Rectangular, sealed enclosure
Enclosure Material:	Hardwood multi-ply plywood
Finish:	Black or White (custom colors available)
Connectors:	2-pole Phoenix
Suspension Hardware:	(2) 1/4"-20 threaded mounting points

NOMINAL DATA

Frequency Response:	45 – 350 Hz \pm 3 dB
Nominal Impedance:	4 Ω (16 Ω available)
Power Handling:	350 W long term (AES-2)
Maximum Long-Term Output: Peak Output:	108 dB 112 dB
Dimensions	Height: 23.75" / 603 mm Width: 23.75" / 603 mm Depth: 4.75" / 121 mm
Net Weight:	31 lbs / 14.1 kg
Shipping Weight:	35 lbs / 15.9 kg

Micro-Sub 2x6C

Micro-Sub Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

