

SB-115

Sub-Bass Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

Installation Sub-Woofers

DESCRIPTION

The **SB-115** is a very compact sub-bass module designed for permanent installation. It employs a 15-inch long-excursion driver in an optimally tuned vented enclosure which can be suspended from internal fly points or positioned on the floor.

The **SB-115** is an ideal choice for applications requiring precise transient response and low bass extension. Its compact size fits well under stages, on stage, and in flown arrays.



KEY FEATURES

- Compact size
- Bass extension to 34 Hz
- Very high output
- Excellent transient response

APPLICATIONS

- Churches
- Performing Arts Centers
- Cinema
- Night Clubs

DESCRIPTIVE DATA

System Configuration:	Dedicated sub-bass
Components & Loading:	(1) 15" long-excursion cone driver
Recommended High-Pass Filter:	4 th order Butterworth @ 34 Hz
Input Connectors:	NL-4 & dual binding head screws
Enclosure Type:	Optimally tuned, vented
Enclosure Material:	Hardwood multi-ply plywood
Finish:	Black or White standard (custom colors available)
Suspension Hardware:	(8) 3/8-16 threaded mounting points located on enclosure top, sides & back
Grille:	Painted perforated steel

NOMINAL DATA

Frequency Response:	34 – 350 Hz \pm 3 dB
Sensitivity:	95 dB @ 2.83 volts / 1M (in operating band)
Impedance:	8 Ω
Power Handling:	1000 W long-term (AES-2)
Maximum Long-Term Output:	123 dB @ 1M
Peak Output:	129 dB @ 1M
Nominal Coverage Angles:	Omni-directional
Dimensions	Height: 17.25" / 438 mm
	Width: 17.25" / 438 mm
	Depth: 27.63" / 702 mm
Net Weight:	90 lbs. / 40.9 kg
Shipping Weight:	117 lbs. / 53.2 kg

SB-115

Sub-Bass Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

