SB-118

Sub-Bass Series



Installation Sub-Woofers

DESCRIPTION

The **SB-118** is a very compact sub-bass module designed for permanent installation. It employs an 18-inch long-excursion driver in an optimally tuned vented enclosure which can be suspended from internal fly points or positioned on the floor.

The **SB-118** is an ideal choice for applications requiring precise transient response and low bass extension. Its compact size fits well under stages, on stage, and in flown arrays.



KEY FEATURES

Compact size

- Very high output
- Excellent transient response

APPLICATIONS

- Churches
- Performing Arts Centers
- Cinema
- Night Clubs


DESCRIPTIVE DATA

System Configuration:	Dedicated sub-bass
Components & Loading:	(1) 18" long-excursion cone driver
Recommended High-Pass Filter:	4 th order Butterworth @ 22 Hz
Input Connectors:	NL-4 & dual binding head screws
Enclosure Type:	Optimally tuned, vented
Enclosure Material:	Hardwood multi-ply plywood
Finish:	Black or White standard (custom colors available)
Suspension Hardware:	(8) 3/8-16 threaded mounting points located on enclosure top, sides & back
Grille:	Painted perforated steel

NOMINAL DATA

Frequency Response:		28 – 350 Hz ±3 dB
Sensitivity:		97 dB @ 2.83 volts / 1M (in operating band)
Impedance:		8 Ω
		1200 W long-term (AES-2)
Maximum Long-Term Output: Peak Output:		127 dB @ 1M 133 dB @ 1M
		Omni-directional
Dimensions	Height: Width: Depth:	19.69" / 500 mm 21.07" / 535 mm 30.60" / 777 mm
		104 lbs / 47.3 kg
		134 lbs / 60.9 kg

SB-118





DIMENSIONAL DRAWINGS

