

SL-1.1 R

Slim Line Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

Slim Profile Surface Mount Loudspeakers

DESCRIPTION

Slim Line surface-mount loudspeakers have a very thin profile (2" D or less) and are ideal for nearfield applications. They are voiced to deliver an accurate neutral sound.

The **SL-1.1 R** is a slim 2-way loudspeaker designed to be surface-mounted and disappear into the architectural surroundings. It employs a 1" textile dome HF driver and a 4" long-excursion LF driver to yield a very smooth, neutral response for near-field applications.



KEY FEATURES

- 120° H x 120° V Coverage
- Very Slim Profile (only 2" deep by 4" wide)
- Blends into architectural environment

APPLICATIONS

- Home Theater LCR
- Home Theater Surrounds
- Compact Personal Monitor

DESCRIPTIVE DATA

System Configuration:	Low profile 2-way
Components & Loading:	(1) 4" long-excursion LF driver; (1) 1" textile dome HF driver
High-Pass Filter:	Built-in 1 st order @ 130 Hz
Enclosure Type:	Sealed enclosure, very low profile
Enclosure Material:	Steel chassis, with composite endcaps
Finish:	Black or White standard (custom colors available)
Connectors:	Phoenix
Suspension Hardware:	Mounting brackets included
Grille:	Integral, fabric wrapped

NOMINAL DATA

Frequency Response:	130 – 20,000 Hz ±3 dB
Sensitivity:	89 dB @ 2.83 volts / 1M
Nominal Impedance:	8 Ω (70-volt transformer available)
Power Handling:	45 W long term program (AES-2)
Maximum Long-Term Output:	103 dB @ 1 meter
Peak Output:	109 dB @ 1 meter
Nominal Coverage Angles:	120° H x 120° V
Dimensions	Height: 10.50" / 267 mm
	Width: 4.56" / 116 mm
	Depth: 2.06" / 52 mm
Net Weight:	4.2 lbs / 1.9 kg
Shipping Weight:	5.2 lbs / 2.4 kg

SL-1.1 R

Slim Line Series



EXPERIENCE THE SOUND
OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

