

# SL-1.1 US

Slim Line Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## Slim Profile Surface Mount Loudspeakers

### DESCRIPTION

Slim Line surface-mount loudspeakers have a very thin profile and are ideal for nearfield applications. They are voiced to deliver an accurate neutral sound.

The **SL-1.1 US** is an ultra-slim 2-way loudspeaker designed to be surface-mounted flat on a wall and disappear into the architectural surroundings. It employs a 1" textile dome HF driver and a 4" long-excursion LF driver to yield a very smooth, neutral response for near-field applications.



### KEY FEATURES

- 120° H x 120° V Coverage
- On-wall mounting
- Ultra-thin Profile (only 1.75" deep)
- Blends into architectural environment
- Hidden Mounting Bracket

### APPLICATIONS

- Sound for Video Presentations
- Home Theater L-C-R
- Home Theater Surrounds
- Spot Fill in Larger Sounds Systems

### DESCRIPTIVE DATA

System Configuration:	Low profile 2-way
Components & Loading:	(1) 4" long-excursion LF driver; (1) 1" textile dome HF driver
High-Pass Filter:	Built-in 1 <sup>st</sup> order @ 130 Hz
Enclosure Type:	Sealed enclosure, very low profile
Enclosure Material:	Steel chassis, with composite endcaps
Finish:	Black or White standard (custom colors available)
Connectors:	Phoenix
Suspension Hardware:	Hidden mounting plate
Grille:	Integral, fabric wrapped

### NOMINAL DATA

Frequency Response:	130 – 20,000 Hz ±3 dB
Sensitivity:	89 dB @ 2.83 volts / 1M
Nominal Impedance:	8 Ω (70-volt transformer available)
Power Handling:	45 W long term program (AES-2)
Maximum Long-Term Output:	103 dB @ 1 meter
Peak Output:	109 dB @ 1 meter
Nominal Coverage Angles:	120° H x 120° V
Dimensions	Height: 11.00" / 279 mm
	Width: 6.75" / 171 mm
	Depth: 1.75" / 44 mm
Net Weight:	4.2 lbs / 1.9 kg
Shipping Weight:	5.2 lbs / 2.4 kg

# SL-1.1 US

Slim Line Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## DIMENSIONAL DRAWINGS

