

# SL-2.1 US

## Slim Line Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## Slim Profile Surface Mount Loudspeakers

### DESCRIPTION

Slim Line surface-mount loudspeakers have a very thin profile and are ideal for nearfield applications. They are voiced to deliver an accurate neutral sound.

The **SL-2.1 US** is an ultra-slim 2-way loudspeaker designed to be surface-mounted flat on a wall and disappear into the architectural surroundings. Its precision ribbon HF driver and two 4" long-excursion LF drivers resolve complex audio program with detail and clarity that does not seem possible from such a small package.



### KEY FEATURES

- 120° H x 90° V Coverage
- Very Slim Profile (only 1.75" deep)
- Flat on-wall mounting
- Blends into architectural environment

### APPLICATIONS

- Sound for Video Presentation
- Home Theater LCR
- Home Theater Surrounds

### DESCRIPTIVE DATA

System Configuration:	Low profile 2-way
Components & Loading:	(2) 4" long-excursion LF drivers; 1 ribbon HF driver
High-Pass Filter:	Built-in 1 <sup>st</sup> order @ 130 Hz
Enclosure Type:	Sealed enclosure, very low profile
Enclosure Material:	Steel chassis, with composite endcaps
Finish:	Black or White standard (custom colors available)
Connectors:	Phoenix
Suspension Hardware:	Hidden mounting plate
Grille:	Integral, fabric wrapped

### NOMINAL DATA

Frequency Response:	120 – 20,000 Hz ±3 dB
Sensitivity:	92 dB @ 2.83 volts / 1M
Nominal Impedance:	6 Ω (70-volt transformer available)
Power Handling:	90 W long term program (AES-2)
Maximum Long-Term Output: Peak Output:	108 dB @ 1 meter 114 dB @ 1 meter
Nominal Coverage Angles:	120° H x 90° V
Dimensions	Height: 18.50" / 470 mm Width: 6.75" / 171 mm Depth: 1.75" / 44 mm
Net Weight:	7 lbs / 3.2 kg
Shipping Weight:	8 lbs / 3.6 kg

# SL-2.1 US

Slim Line Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## DIMENSIONAL DRAWINGS

