

# SL-4.1 R



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## Slim Line Series

### Slim Profile Surface Mount Loudspeakers

#### DESCRIPTION

Slim Line surface-mount loudspeakers have a very thin profile (2" D or less) and are ideal for nearfield applications. They are voiced to deliver an accurate neutral sound.

The **SL-4.1 R** is a slim 2-way loudspeaker designed to be surface-mounted and disappear into the architectural surroundings. Its precision ribbon HF driver and four 4" long-excursion LF drivers resolve complex audio program with detail and clarity that does not seem possible from such a small package.



#### KEY FEATURES

- 120° H x 90° V Coverage
- Very Slim Profile (only 2" deep by 4" wide)
- Employs precision ribbon HF driver
- Easily integrated into architectural casework with optional millwork adapterkit

#### APPLICATIONS

- Sound for Video Presentation
- Home Theater LCR
- Home Theater Surrounds
- Delay Fill

#### DESCRIPTIVE DATA

System Configuration:	Low profile 2-way
Components & Loading:	(4) 4" long-excursion LF drivers; 1 ribbon HF driver
High-Pass Filter:	Built-in 1 <sup>st</sup> order @ 130 Hz
Enclosure Type:	Sealed enclosure, very low profile
Enclosure Material:	Steel chassis, with composite endcaps
Finish:	Black or White standard (custom colors available)
Connectors:	Phoenix
Suspension Hardware:	Mounting brackets included
Grille:	Integral, fabric wrapped

#### NOMINAL DATA

Frequency Response:	120 - 20,000 Hz ±3 dB
Sensitivity:	92 dB @ 2.83 volts / 1M
Nominal Impedance:	8 Ω (70-volt transformer available)
Power Handling:	150 W long term program (AES-2)
Maximum Long-Term Output:	111 dB @ 1 meter
Peak Output:	117 dB @ 1 meter
Nominal Coverage Angles:	120° H x 90° V
Dimensions	Height: 30.50" / 775 mm
	Width: 4.56" / 116 mm
	Depth: 2.06" / 52 mm
Net Weight:	11.0 lbs / 5.0 kg
Shipping Weight:	13.9 lbs / 6.3 kg

# SL-4.1 R

Slim Line Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## DIMENSIONAL DRAWINGS

