

# SL-Micro

Slim Line Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## Slim Profile Surface Mount Loudspeakers

### DESCRIPTION

Slim Line surface-mount loudspeakers have a very thin profile (2" D or less) and are ideal for nearfield applications. They are voiced to deliver an accurate neutral sound.

The **SL-Micro** is a slim 2-way loudspeaker designed to be surface- or flush-mounted and disappear into the architectural surroundings. It employs a 3/4" textile dome HF driver and two 2" long-excursion LF drivers to yield a very smooth, neutral response for near-field applications.



### KEY FEATURES

- 120° H x 90° V Coverage
- Very Slim Profile (only 2" deep by 2.5" wide)
- Easily integrated into architectural casework with optional millwork adapter kit

### APPLICATIONS

- Sound for Video Presentation
- Video Conferencing
- Compact Personal Monitor

### DESCRIPTIVE DATA

System Configuration:	Low profile 2-way
Components & Loading:	(2) 2" long-excursion LF drivers; (1) 3/4" textile dome HF driver
High-Pass Filter:	Built-in 1 <sup>st</sup> order @ 150 Hz
Enclosure Type:	Sealed enclosure, very low profile
Enclosure Material:	Steel chassis, with composite endcaps
Finish:	Black or White standard (custom colors available)
Connectors:	Phoenix
Suspension Hardware:	Mounting brackets included
Grille:	Perforated metal

### NOMINAL DATA

Frequency Response:	150 – 20,000 Hz ±3 dB
Sensitivity:	84 dB @ 2.83 volts / 1M
Nominal Impedance:	8 Ω (70-volt transformer available)
Power Handling:	45 W long term program (AES-2)
Maximum Long-Term Output: Peak Output:	100 dB @ 1 meter 106 dB @ 1 meter
Nominal Coverage Angles:	120° H x 90° V
Dimensions	Height: 13.00" / 330 mm Width: 2.50" / 64 mm Depth: 2.00" / 51 mm
Net Weight:	4 lbs / 1.8 kg
Shipping Weight:	5 lbs / 2.3 kg

# SL-Micro

Slim Line Series



EXPERIENCE THE SOUND  
OF TRUE ENGAGEMENT

## DIMENSIONAL DRAWINGS

