SLA-4.1



Frequency Shaded Line Array Series

EXPERIENCE THE SOUND OF TRUE ENGAGEMENT

True Sound Engagement in Challenging Acoustics

DESCRIPTION

The **SLA-4.1** is a high output Frequency Shaded Line Array loudspeaker employing a ribbon HF driver and four 4" LF drivers within a very slim profile enclosure. It is designed to work in highly reverberant environments where its broad 120° horizontal coverage and a focused 25° vertical pattern are beneficial.

A sophisticated filter circuit sequentially integrates drivers in the array to maintain pattern control to 900 Hz and ensures a smooth transition from line-source to point-source behavior at lower frequencies. The result is very flat response and uniform pattern control, yielding superior speech clarity and musical detail.



KEY FEATURES

APPLICATIONS

- 120° H x 25° V Coverage
- Maintains 25° Vertical Pattern to 900Hz
- Low Profile (only 3.4" deep)
- Optimized for Speech

- Churches
 - Classrooms
 - Lecture Halls
 - Presentation spaces

DESCRIPTIVE DATA

	Compact frequency-shaded line array
	(4) 4" LF drivers; (1) ribbon HF driver
	4 th order Butterworth @ 100 Hz
Enclosure Type:	Sealed enclosure, low profile column
Enclosure Material:	Steel, with composite endcaps
	Black or White standard (custom colors available)
Connectors:	NL-4 & dual binding-head screws
	(10) 1/4-20 threaded points on back and endcaps – OmniMount 25.0 series compatible (slotted yoke bracket included)
	Integral, fabric wrapped

NOMINAL DATA

		120 – 20,000 Hz ±3 dB
		95 dB @ 2.83 volts / 1M
Nominal Impedance:		4 Ω (70-volt available)
		175 W long term (AES-2)
Maximum Long-Term Output: Peak Output:		116 dB 122 dB
		120° H x 25° V
Dimensions	Height: Width: Depth:	25.62" / 651 mm 5.62" / 143 mm 3.38" / 86 mm
		15 lbs / 6.8 kg
Shipping Weight:		18 lbs / 8.2 kg

SLA-4.1



Frequency Shaded Line Array Series

DIMENSIONAL DRAWINGS







