## ULA-16.16

## Uniform Line Array Series



### True Sound Engagement in Large Venues

#### **DESCRIPTION**

The **ULA-16.16** is a very slim profile continuous line array (3" x 6" in cross section) with a uniform 120° H x 8° V coverage pattern. Each ULA-16.16 employs sixteen 3.5" long-excursion LF drivers and sixteen 3" precision HF ribbon elements with a passive crossover network.

It has been designed to be used both as a single loudspeaker for medium-throw applications and stacked in multiples to create large arrays for very long-throw applications.

The **ULA-16.16** can also be used in combination with Innovox DLF Series dipole steered low-frequency loudspeakers to create a powerful, compact full-range music system.



#### **KEY FEATURES**

- Slim Profile 3" D x 8" W
- 120° H x 8° V coverage pattern
- Line behavior to 500Hz (single array)
- Can be stacked to form longer arrays

#### **APPLICATIONS**

- Churches
- Performing Arts Centers
- Cinemas
- Transit Centers

#### **DESCRIPTIVE DATA**

System Configuration:	Continuous full-range line array
Components & Loading:	(16) 3.5" long-excursion LF drivers; (16) 3.2" ribbon HF drivers
Recommended High-Pass Filter:	4 <sup>th</sup> order Butterworth @ 100 Hz
Input Connectors:	NL-4 & dual binding head screws
Enclosure Type:	Sealed enclosure
Enclosure Material:	Steel, with composite endcaps
Finish:	Black or White standard (custom colors available)
Suspension Hardware:	(4) 1/4-20 points in rear corners; OmniMount 120.0 Series compatible
Grille:	Integral fabric wrap around steel chassis

#### **NOMINAL DATA**

Frequency Response:		120 – 20,000 Hz ±3 dB
Sensitivity:		94 dB @ 2.83 volts / 1M
Impedance:		8 Ω
Power Handling:		500 W long-term (AES-2)
Maximum Long-Term Output:		120 dB @ 1M
Peak Output:		126 dB @ 1M
Nominal Coverage Angles:		120° H x 8° V
Vertical Directivity to:		460 Hz
Dimensions		58.63" / 1489 mm
		6.0" / 152 mm
	Depth:	3.0" / 76 mm
		29.5 lbs / 13.4 kg
Shipping Weight:		35 lbs / 15.9 kg

# ULA-16.16





#### **DIMENSIONAL DRAWINGS**

-  6.66 [169.04]	[a.19]		
		i di i	
58.43 165 [1469.06] 165 [2469.06]			
		. E	