

## Compact Powered Sub-Bass Loudspeaker

The Micro-Sub 12P is a high definition powered subwoofer designed for permanent installation. It uses a 12" low frequency driver in a compact sealed enclosure and employs a 200-Watt PowerSoft Class D amplifier to achieve superior transient response and maximum output.

The Micro-Sub 12P complements the Innovox Slim Line and SLA Series of shallow profile surface-mount loudspeakers, and the Flex Video Series of display-mounted loudspeakers. It also is used as a low-bass component in extended range distributed audio systems.



### Key Features

- Very Compact Enclosure (only 9" deep)
- Excellent Transient Response
- LF Extension to 32 Hz

### Applications

- Sound for Video Presentations
- Themed Venues and Restaurants
- Boardrooms
- Retail Spaces
- Video Wall Installations

## Technical Specifications

### DESCRIPTIVE DATA

System configuration	Dedicated low frequency
Components & Loading	(1) 12" LF drivers
Recommended High-Pass	4th order Butterworth @ 35 Hz
Nominal Impedance	4 $\Omega$
Input Connectors	(1) 3-pole Phoenix
Enclosure Material	Hardwood multi-ply plywood
Enclosure Type	Rectangular, sealed enclosure
Finish	Black or white standard (custom colors available)
Grille	Painted, perforated steel
Suspension Hardware	(6) 3/8"-16 threaded mounting points

### ACOUSTICAL DATA

Frequency Response	32 Hz--350 Hz $\pm$ 3dB
Class D Power	200 W RMS
Maximum Long-term Output	117 dB
Peak Output	123 dB

### PHYSICAL

Height	23.125" / 587 mm
Width	14.625" / 371 mm
Depth	9.00" / 229 mm
Net Weight	43 lbs. / 19.5 kg
Shipping Weight	47 lbs. / 21.4 kg

Dimensional Drawings

