

Compact Powered Sub-Bass Loudspeaker

The Micro-Sub 12P is a high definition powered subwoofer designed for permanent installation. It uses a 12" low frequency driver in a compact sealed enclosure and employs a 200-Watt PowerSoft Class D amplifier to achieve superior transient response and maximum output.

The Micro-Sub 12P complements the Innovox Slim Line and SLA Series of shallow profile surface-mount loudspeakers, and the Flex Video Series of display-mounted loudspeakers. It also is used as a low-bass component in extended range distributed audio systems.



Key Features

- Very Compact Enclosure (only 9" deep)
- Excellent Transient Response
- LF Extension to 32 Hz

Applications

- Sound for Video Presentations
- Themed Venues and Restaurants
- Boardrooms
- Retail Spaces
- Video Wall Installations

Technical Specifications

| DESCRIPTIVE DATA | |
|-----------------------|---|
| System configuration | Dedicated low frequency |
| Components & Loading | (1) 12" LF drivers |
| Recommended High-Pass | 4th order Butterworth @ 35 Hz |
| Nominal Impedance | 4 Ω |
| Input Connectors | (1) 3-pole Phoenix |
| Enclosure Material | Hardwood multi-ply plywood |
| Enclosure Type | Rectangular, sealed enclosure |
| Finish | Black or white standard (custom colors available) |
| Grille | Painted, perforated steel |
| Suspension Hardware | (6) 3/8"-16 threaded mounting points |

| ACOUSTICAL DATA | |
|--------------------------|--------------------|
| Frequency Response | 32 Hz--350 Hz ±3dB |
| Class D Power | 200 W RMS |
| Maximum Long-term Output | 117 dB |
| Peak Output | 123 dB |

| PHYSICAL | |
|-----------------|-------------------|
| Height | 23.125" / 587 mm |
| Width | 14.625" / 371 mm |
| Depth | 9.00" / 229 mm |
| Net Weight | 43 lbs. / 19.5 kg |
| Shipping Weight | 47 lbs. / 21.4 kg |

Dimensional Drawings

