

Slim Profile Surface Mount Loudspeakers

Slim Line surface-mount loudspeakers have a very thin profile (2" D or less) and are ideal for nearfield applications. They are voiced to deliver an accurate neutral sound. The **SL-2.1 R** is a slim 2-way loudspeaker designed to be surface mounted and disappear into

the architectural surroundings. Its precision ribbon HF driver and two 4" long-excursion LF drivers resolve complex audio program with detail and clarity that does not seem possible from such a small package.



Key Features

- 120° H x 90° V Coverage
- Very Slim Profile (only 2" deep by 4" wide)
- Ribbon HF driver
- Blends into architectural environment

Applications

- Home Theater LCR
- Home Theater Surrounds
- Compact Personal Monitor

Technical Specifications

DESCRIPTIVE DATA

System configuration	Low profile 2-way
Components & Loading	(2) 4" long-excursion LF drivers; 1 ribbon HF driver.
Nominal Impedance	6 Ω (70-volt transformer available)
High-Pass Filter	Built-in 1st order @ 130 Hz
Input Connectors	Phoenix
Enclosure Material	Steel chassis, with composite endcaps
Enclosure Type	Sealed enclosure, very low profile
Finish	Black or white standard (custom colors available)
Grille	Integral, fabric wrapped
Suspension Hardware	Mounting brackets included

ACOUSTICAL DATA

Frequency Response	120 Hz--20 KHz ±3dB
Sensitivity	92 dB @ 2.83 volts / 1M
Power Handling	90 W long term program (AES-2)
Nominal Coverage	120° H x 90° V
Maximum Long-term Output	108 dB @ 1 meter
Peak Output	114 dB @ 1 meter

PHYSICAL

Height	18.00" / 457 mm
Width	4.56" / 116 mm
Depth	2.06" / 52 mm
Net Weight	7 lbs. / 3.2 kg
Shipping Weight/pair (varies with length)	8 lbs. / 2.6 kg

Dimensional Drawings

