



## Description

### SLF-212 Compact Sealed Sub-Bass Loudspeaker

The SLF-212 is a compact, sealed sub-bass loudspeaker featuring two high-performance, long-excursion 12" drivers housed in a robust 0.75" Baltic birch enclosure. It's finished in a durable Warnex textured coating, available in standard black or white, with custom colors offered to blend seamlessly into surrounding architecture.

Engineered to extend the low-frequency response of our CLA and HLA loudspeaker families, the SLF-212's sealed design delivers

#### Key Features

- Sealed enclosure
- Exceptional transient response (musical detail)
- Perfect companion to CLA and HLA
- Available in a variety of finishes

exceptional transient response while maintaining usable frequency extension well below 40 Hz.

For flexible installation, the SLF-212 includes an extensive array of 3/8"-16 fly points on all surfaces, allowing for easy and secure rigging in a variety of configurations.

## Applications

- Houses of worship
- Auditoriums
- Multipurpose meeting venues
- Places of gathering, lobbies
- Corporate gathering spaces
- Higher education / K12

## Nominal Data

Frequency Response	35Hz—150Hz +/- 3dB <sup>1</sup>
Power Handling (AES-2)	800W
Impedance	4 Ohm
Sensitivity	100dB / 1W/1M
Max Long-Term SPL	129dB
Max Peak SPL	132dB
Dimensions (HxWxL)	28.63" [727.08mm] x 15.94" [404.88mm] x 12.24" [311mm]
Net Weight	84 lbs. / 38 kg
Shipping Weight	100 lbs. / 45 kg

## Descriptive

System Configuration	Sealed Sub-Base
Recommended filters	HPF BW48@35Hz, LPF LR24 70-125Hz
Component Loading	Two 12" Low-frequency drivers
Input Configuration	Speakon NL4 x 1, 2POL PHX x 1
Enclosure Type	Sealed
Enclosure Materials	Baltic Birch, .75"
Finish	Warnex texture - perforated metal grille <sup>1</sup>
Suspension Hardware	3/8-16 Fly-points x 10

<sup>1</sup> Requires factory preset

<sup>1</sup> Standard color is black, custom colors are available upon request, upcharge will apply

Technical Drawings

