

## Vertical Line Array Solution for Larger Rooms

The **FF-V2 8698 P** loudspeaker pairs use shaded line array technology with ribbon high frequency drivers to extend sound projection in longer rooms. Its frequency response (120 Hz - 20 kHz ±3dB) is optimized for speech intelligibility and musical

detail. **FF-V2 8698 P** loudspeakers can be used in combination with an Innovox Micro-Sub Series sub-woofer to extend low frequency response to support full-range music program. The **FF-V2 8698 P** employs a 100 watt amplifier.



### Key Features

- *Made To Match Height Of Video Display*
- *Onboard 100-Watt Class D Amplifier*
- *Ribbon Hf Driver Provides Speech Clarity*
- *Precise 120° H X 25° V Control*
- *Line Array Projection For Longer Rooms*

### Applications

- *Stereo Video Conference Speaker*
- *Audio To Compliment Digital Signage*
- *2.1 System In Combination With Microsub Subwoofer*
- *Audio For High End Video Displays*

## Technical Specifications

### DESCRIPTIVE DATA

<b>System configuration</b>	Frequency-shaded line array (sold in pairs)
<b>Components &amp; Loading</b>	(6) 3.5" LF drivers; (1) ribbon HF driver.
<b>Nominal Impedance</b>	8Ω
<b>Input Connectors</b>	2-pole Phoenix
<b>Enclosure Material</b>	Extruded ABS plastic with ABS endcaps
<b>Enclosure Type</b>	Sealed enclosure, low profile column
<b>Finish</b>	Black fabric
<b>Grille</b>	Integral, fabric wrap, color black
<b>Suspension Options</b>	#1 - Adjustable universal bracket for direct mount to display #2 - Wall-mount

### ACOUSTICAL DATA

<b>Frequency Response</b>	120 Hz--20 KHz ±3dB
<b>Sensitivity</b>	95 dB @ 2.83 volts / 1M
<b>Pattern Control to</b>	650 Hz
<b>Nominal Coverage</b>	120° H x 25° V
<b>Long Term Power Handling</b>	200 W (AES-2)
<b>Maximum Long-term Output</b>	116 dB
<b>Peak Output</b>	122 dB

### PHYSICAL

<b>Minimum Display Height</b>	37" / 940 mm
<b>Height</b>	(custom)
<b>Width</b>	4.06" / 103 mm
<b>Depth</b>	2.13" / 54 mm
<b>Net Weight/pair (varies with length)</b>	14.0-31 lbs. / 3.7-14.1 kg
<b>Shipping Weight/pair (varies with length)</b>	18.0-35.0 lbs. / 8.2-15.9 kg

Dimensional Drawings

