

## Made-to-Measure for the Exact Width of Your Flat Panel Display

The **Flex Precision FP-V2 5570** is a display mounted single-channel horizontal loudspeaker that employs ribbon HF and extended range LF drivers in an ultra slim enclosure. Its frequency response (120-20,000 Hz 3 dB) has been optimized for speech intelligibility.

Flex Precision loudspeakers can be used in combination with an Innovox Micro-Sub Series sub-woofer to extend low frequency response below 50 Hz to support full-range music program.



### Key Features

- *Made To Match The Height Of The Display*
- *Works With Micro-Sub Series Subwoofers*
- *Ribbon Hf Driver Provides Speech Clarity*

### Applications

- *Stereo Video Conference Speaker*
- *Audio For Digital Signage*
- *Uniform Sound Coverage For Near-Field Applications*

## Technical Specifications

### DESCRIPTIVE DATA

<b>System configuration</b>	Frequency-shaded line array (sold in pairs)..
<b>Components &amp; Loading</b>	(4) 3.5" long-excursion LF drivers; (1) 3.25" ribbon HF driver.
<b>Recommended High-Pass</b>	4th order Butterworth @100 Hz
<b>Input Connectors</b>	2-pole Phoenix
<b>Enclosure Material</b>	Extruded ABS plastic with steel baffle plate.
<b>Enclosure Type</b>	Sealed enclosure, low profile column
<b>Finish</b>	Black fabric
<b>Grille</b>	Integral, fabric wrap, color black
<b>Suspension</b>	Adjustable universal mounting system for direct mount to display.

### ACOUSTICAL DATA

<b>Frequency Response</b>	120 Hz--20 KHz $\pm$ 3dB
<b>Coverage</b>	120° H x 90° V
<b>Long-term Output</b>	105 dB
<b>Peak Output</b>	111 dB
<b>Sensitivity</b>	92 dB @ 2.83 volts / 1M
<b>Impedance</b>	6 $\Omega$ per channel
<b>Power Handling</b>	90 W (AES-2) per channel

### PHYSICAL

<b>Maximum Height</b>	18.0" / 457 mm
<b>Height</b>	(custom)
<b>Width</b>	4.06" / 103 mm
<b>Depth</b>	2.13" / 54 mm
<b>Net Weight/pair</b> (varies with length)	9 - 26 lbs. / 4.0 - 11.7 kg
<b>Shipping Weight/pair</b> (varies with length)	13 - 30 lbs. / 5.8 - 13.6 kg

Dimensional Drawings

